



P68F III series

CARICO STATICO / STATIC LOAD

6000 KG

MOTORI / MOTORS

4 POLI 50Hz

CARICO UTILE / LOAD CAPACITY

RIDUZIONE RATIO	PULEGGIA SHEAVE DIA/mm	VELOCITÀ SPEED m/sec	HP	HP	HP	HP	HP	
			8 Kg	10 Kg	12 Kg	14 Kg	16 Kg	
69:1	520	0.54-0.59	720					
	550	0.57-0.62	670					
	600	0.62-0.68	610					
	650	0.67-0.74	560					
62:1	520	0.60-0.66	720	840				
	550	0.63-0.70	680	780				
	600	0.69-0.76	610	720				
	650	0.75-0.82	560	660				
52:1	520	0.71-0.78	630	800				
	550	0.75-0.83	590	750				
	600	0.82-0.90	530	680				
	650	0.89-0.98	480	620				
44:1	520	0.84-0.93		720	880			
	550	0.89-0.98		680	840			
	600	0.97-1.07		610	760			
	650	1.05-1.16		560	700			
38:1	520	0.97-1.07		640	780	940	1040	
	550	1.03-1.14		600	740	880	980	
	600	1.12-1.24		540	670	800	880	
	650	1.22-1.34		490	620	730	800	
60:2	520	1.23-1.36			700	850	940	
	550	1.30-1.44			660	800	880	
	600	1.42-1.57			600	720	790	
	650	1.54-1.70			550	660	720	
43:2	520	1.72-1.90			530	620	680	
	550	1.82-2.01			490	580	640	
	600	1.99-2.19			450	520	570	
	650	2.15-2.37			400	480	520	

MOTORI / MOTORS

6 POLI 50Hz

CARICO UTILE / LOAD CAPACITY

RIDUZIONE RATIO	PULEGGIA SHEAVE DIA/mm	VELOCITÀ SPEED m/sec	HP	HP	HP	HP	HP	
			6 Kg	7 Kg	8 Kg	9 Kg	10 Kg	
69:1	520	0.37-0.39	680					
	550	0.39-0.42	650					
	600	0.42-0.45	620					
	650	0.46-0.49	600					
62:1	520	0.41-0.44	760	800				
	550	0.43-0.46	720	760				
	600	0.47-0.51	660	700				
	650	0.51-0.55	600	640				